

M-119 LV

DESCRIPTION

M-119 LV is a water based corrosion inhibitor for use in water based epoxies, urethanes, acrylics and alkyds. M-119 LV provides protection for carbon steel and aluminum, eliminates in-can corrosion and reduces scribe creep. M-119 LV does not contain any heavy metals such as zinc phosphate, chromates or barium. M-119 LV works in both the vapor and contact phases.

UFI: Y550-7021-P00E-CAU3

PACKAGING & STORAGE

M-119 LV is available in 5 gallon (19 L) pails, 55 gallon (208 L) metal drums, liquid totes, and bulk.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years



CHARACTERISTICS/TECHNICAL DATA

Appearance	Tan liquid
% Solids by Weight	35-42%
VOCs (ASTM D3960)	2.9 lbs/gal (350 g/L)
Density	7.8-8.2 lbs/gal (.9398 kg/L)
pH (Neat)	8.2-9.2

APPLICATION

Recommended loading levels range from 1.0 – 3.0% based on total formula weight.

Coatings

Grind Base/Mill Base

- Water Grind w/o Resin add after wetting agent & co-solvents are added
- Water Grind w/ Resin add to resin prior to adding other components

Post Add

- Letdown add into letdown using moderate to high agitation
- Post add add into final product using moderate to high agitation

4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC info@cortecvci.com https://www.cortecvci.com https://www.cortecadditives.com







All statements, technical information and recommendations contained herein are based on tests Cortec* Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC* CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Revised: 02/23/21. Supersedes: 02/27/18. ©Cortec Corporation 2021 of Cortec® Corporation. All Rights Reserved. Copying and/or manipulation of these materials in any form without the written authorization of Cortec® Corporation is strictly prohibited. 2021 ©Cortec® Corp. ISO accreditation applies to Cortec's processes only.