


# S-10 FA



#### **PRODUCT DESCRIPTION**

S-10FA is a filming amine blend for controlling corrosion in condensate systems by the formation of a protective film on the metal surface.

This filming amine blend when added to the steam line volatilizes with the steam and then deposits in the form of a coating.

S-10FA has a double bond in its molecules. Such molecular structure helps to increase its solubility.

S-10FA is a hydrocarbon soluble, water dispersible product that will protect condensate systems from aggressive carbon dioxide and oxygen attacks. For the best results, it is recommended to be injected continuously in steam overheads or ahead of any existing areas where corrosion can occur.

# **FEATURES**

- Economical
- Compatible with most other treatment products
- High efficiency against oxygen and low pH
- Thermally stable

# **TYPICAL PROPERTIES**

Appearance Odor Density

liquid Amine 7.0-7.4 lb/gal (0.83-0.88kg/l)

Clear to hazy light yellow

# DOSAGE

A typical dose is 10 ppm to boiler feed water. It is recommended to add S-10FA to the steam header. The dose can be adjusted depending on actual pH level and oxygen content in condensate.

#### PACKAGING AND STORAGE

S-10 FA is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. The shelf life for S-10FA is 2 years in closed original container.



FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN KEEP CONTAINER TIGHTLY CLOSED NOT FOR INTERNAL CONSUMPTION CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

#### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within as months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.cortecvci.com

printed on recycled paper 100% post consumer Revised: 12/31/13. ©Cortec Corporation 2009-2013. All rights reserved. Supersedes: 7/15/09. © 2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only. Distributed by: